

# Enhanced Source Removal Using In-Situ Chemical Flushing

#### A. Lynn Wood

U.S. Environmental Protection Agency National Risk Management Research Laboratory

## **Outline**



- Description of in-situ chemical flushing
- Effectiveness for DNAPL removal
- Benefits of DNAPL mass reduction
- Integrated source remediation with ISCF

# In-Situ Chemical Flushing



#### Definition


 Displacement of fluid containing chemical adjuvants through contaminated soils or aquifers in order to enhance contaminant removal by enhanced dissolution or mobilization

### Example Adjuvants

- -Surfactants
- -Co-solvents
- -Complex Sugar

# NAPL Removal Effectiveness





# **Efficiency Constraints**



- Hydrodynamic variability
- ✓ DNAPL architecture
- ✓ Remedial fluid properties density viscosity
- Inadequate characterization

Mixing


# Field Results

			EST. Mass
Site	DNAPL	Agent	Reduction
Hill AFB OU2	TCE	Surfactant	0.98
<i>II</i>	TCE	Surfact/foam	0.90
Camp Lejuene	PCE	Surfactant	0.72
Sages	PCE	Cosolvent	0.63
Dover	PCE	Cosolvent	0.64
<i>II</i>	<i>II</i>	Surfactant	0.67
11	"	Cosolvent	?
<i>II</i>	11	Cyclodextrin	?

### Mass Reduction vs Mass Flux








**Most contaminated** 

**Post-Remediation:** 

**Source Zone** 

**Source Zone** 

Least contaminated




Contaminant flux = f(HS, DA)

HS - hydrodynamic structure DA – DNAPL architecture

# Mass Reduction vs Mass Flux





#### PLUME RESPONSE









# Conceptual Model





# Integrated Source Remediation: Chemically Augmented NA (CANA)





#### PLUME RESPONSE **Pre-Remediation:** DNAPL **Dissolved Plume** Source Zone **Control Plane Compliance Plane** Partial Mass Removal: DNAPL **Dissolved Plume** Source Zone **Control Plane Compliance Plane** Partial Mass Removal + Enhanced Natural Attenuation: **DNAPL** Dissolved Plume Source Zone **Control Plane Compliance Plane**

## Integrated Source Remediation:



- Target DNAPL Source Zone
- Integrate Remediation Technologies into a Treatment Train for Comprehensive Site Restoration
- Decrease Remediation Costs

# Integrated Source Remediation: Solvent Extraction Residual Biotreatment (SERB)



#### Field Demonstration: Sages Site

- CoSolvent Extraction (SE)
   Selective removal of DNAPL (PCE)
   by cosolvent flushing with ethanol
- Residual Biotreatment (RB)
   Passive removal of dissolved phase PCE by enhanced reductive dechlorination (biodegradation)

#### Cosolvent Flush Performance\*



Pre-Cosolvent Flush Partitioning Tracer 6

68 L (PCE)

Post-Cosolvent Flush Partitioning Tracer

26 L (PCE)

Estimated Recovery Based on Partitioning Tracer Tests 42 L (PCE)

(62%)

Mass Recovery Based on PCE
Concentrations in Recovery Wells

43 L (PCE) (63%)

Mass Recovery Based on Post/Pre Cores

(65%)


<sup>\*</sup> Jawitz et al., 2000

#### Residual Biotreatment Performance




#### **PCE** (500 uM = 83 mg/L)


#### **Pre-Ethanol Flush**




#### ~1 Month Post-Flush



#### ~13.5 Months Post-Flush



#### ~25 Months Post-Flush



500 uM

450 uM

400 uM

350 uM

300 uM

250 uM

200 uM

150 uM

100 ul

50 uM

0 uM

#### Residual Biotreatment Performance




#### **CIS-DCE** (175 uM = 17 mg/L)


#### **Pre-Ethanol Flush**

# C4 C3 MW-512 MW-514MW-513 MW-505 MW-506 MW-510 MW-507


#### ~1 Month Post-Flush



#### ~13.5 Months Post-Flush



#### ~25 Months Post-Flush



175 uM

150 uM

125 uM

100 uM

75 uM

50 uM


25 uM

0 uM


# OBSERVED PLUME RESPONSE SAGE'S DRY CLEANER SITE





#### **Pre-Ethanol Flush**



#### ~25 Months Post-Flush







# Summary



- Substantial DNAPL mass reduction can be achieved using ISCF
- Complete mass removal is generally not economically or technically feasible
- Correlation between mass reduction and mass flux is poorly understood
- Integrated DNAPL remediation approaches that incorporate technology coupling (treatment trains) are needed to improve efficiency and reduce costs